EXHIBIT 11

JS005987863A

United States Patent [19]

Busboom et al.

[11] Patent Number: 5,987,863

[45] Date of Patent: Nov. 23, 1999

[54]	LAWN MOWER HAVING FLOW CONTROL BAFFLES AND REMOVABLE MULCHING BAFFLES
[75]	Inventore Carry W Dushoom Iohn C

- [75] Inventors: Garry W. Busboom; John C. Crumrine, both of Beatrice, Nebr.
- [73] Assignee: Exmark Mfg. Co., Beatrice, Nebr.
- [21] Appl. No.: 09/135,926
- [22] Filed: Aug. 18, 1998

Related U.S. Application Data

- [63] Continuation of application No. 08/784,825, Jan. 17, 1997, Pat. No. 5,845,475, which is a continuation-in-part of application No. 08/559,575, Nov. 16, 1995, abandoned.
- [51] Int. Cl.⁶ A01D 67/00

56/DIG. 9, 17.5, 17.4, DIG. 20, DIG. 24, DIG. 22

[56] References Cited

U.S. PATENT DOCUMENTS

4,055,036	10/1977	Kidd 56/320.2 X
4,967,543	11/1990	Scag et al 56/10.8
5,077,959	1/1992	Wenzel 56/11.1
5,127,215	7/1992	Wenzel 56/11.1
5,129,217	7/1992	Loehr 56/13.6
5,133,176	7/1992	Baumann et al 56/320.1 X
5,155,985	10/1992	Oshima et al 56/10.8
5,205,112	4/1993	Tillotson et al 56/2
5,210,998	5/1993	Hojo et al 56/320.1 X
5,212,938	5/1993	Zenner et al 56/320.1
5,239,810	8/1993	Gugel 56/10.8
5,249,411	10/1993	Hake 56/11.6
5,251,429	10/1993	Minato et al 56/17.2
5,267,429	12/1993	Kettler et al 56/320.2 X
5,305,589	4/1994	Rodriguez et al 56/320.1
5,337,543	8/1994	Kitamura et al 56/10.8

5,355,661	10/1994	Tomiyama 56/10.8
5,355,664	10/1994	Zenner 56/15.8
5,457,947	10/1995	Samejima et al 56/320.2 X
5,465,564	11/1995	Koehn et al 56/320.2
5,483,790	1/1996	Kuhn et al 56/320.1 X
5,488,821	2/1996	McCunn et al 56/320.1 X
5,518,079	5/1996	Zvolanek 180/19.1
5,609,011	3/1997	Kuhn et al 56/320.1 X
5,628,171	5/1997	Stewart et al 56/320.2
5,765,346	6/1998	Benter et al 56/17.4 X

OTHER PUBLICATIONS

Walker Mowers "Fast, Easy, Beautiful Mowing" Brochure Dec. 1996.

Toro "Groundmaster 580-D" Brochure.

Toro "Groundmaster 300 Series" Brochure.

Toro "Groundmaster 200 Series" Brochure.

Toro "Proline P.O.S." Brochure.

Toro "Landscape Contractor Equipment" Brochure.

Primary Examiner—Victor Batson

Attorney, Agent, or Firm—Zarley, McKee, Thomte, Voorhees & Sease; Dennis L. Thomte

[57] ABSTRACT

A multiblade lawn mower including a mower deck having a plurality of cutting blades rotatably disposed therein. A first flow control baffle is positioned in the mower deck between the cutting blades and the front wall of the mower deck and extends substantially continuously between the sides of the mower deck. A second flow control baffle is positioned in the mower deck rearwardly of the cutting blades. The first and second flow control baffles include a plurality of semicircular baffle portions which define a plurality of open throat portions therebetween. A plurality of selectively removable mulcher baffles are positioned in the mower deck to close the throat portions, thereby defining a substantially cylindrical mulching chamber around each of the cutting blades.

10 Claims, 4 Drawing Sheets

